

SUBDIVISION DESIGN GUIDELINES

FOR

LAKESIDE CROSSING

at

STONEBRIDGE RANCH

**SUBDIVISION DESIGN GUIDELINES
FOR
LAKESIDE CROSSING**

These Subdivision Design Guidelines are designed specifically for LAKESIDE CROSSING Subdivision and are promulgated in accordance with Section 3 of Article VIII of the "Consolidated and Amended Master Declaration of Covenants, Conditions, Restrictions, Easements, Charges and Liens on and for STONEBRIDGE RANCH" (the "Master Declaration") which instrument was recorded on October 29, 1992 as Instrument No. 92-0076613 in the Public Real Estate Records of Collin County, Texas and which is incorporated herein by reference for all purposes.

The primary purpose of these Subdivision Design Guidelines is to supplement the current version of the MASTER DESIGN GUIDELINES for STONEBRIDGE RANCH. Adherence to these guidelines are intended to better assure owners of properties within the LAKESIDE CROSSING Subdivision that all individual improvements will conform to the same high standards of design excellence. The guidelines seek to establish a design framework which the individual homebuilder or homeowner will use as a guide for site improvement, with latitude and flexibility (on the one hand) balanced against preserving the integrity of STONEBRIDGE RANCH (on the other hand). These Subdivision Design Guidelines will, hopefully, serve to guide, inform, aid and inspire to the same extent as they serve to prohibit, restrict and require. While some features are mandated, it should be understood that the Master Architectural Review Committee ("MARC") may make discretionary judgments to reduce or waive any requirement when it can be demonstrated (to the reasonable satisfaction of the MARC) that appropriate mitigating measures have been taken. However, such discretionary approval(s) shall not represent or constitute a binding precedent since no two or more tracts or circumstances are likely to be alike.

1. Height Limitation:

Thirty-five feet (35') measured per City ordinances.

2. Square Footage Requirement:

Minimum Air Conditioned Floor Space: Three thousand (3,000) square feet, inclusive of bonus room.

Exceptions: Three thousand three hundred (3,300) square feet on Lake Lots (Lots 5-17, Block A).

Air Conditioned Square Footage ("ACSF") shall mean the total gross area of the proposed structure, measured from the outside of the exterior wall surface, exclusive of air conditioning duct space, garages, exterior storage, and unfinished attic storage areas not designed to be converted into usable floor area.

3. Minimum Dwelling Setback Requirements:

Front Yard: Twenty-five feet (25') to main structure.

Rear Yard: Twenty-five feet (25') from the rear property line to main structure (excluding accessory buildings, cabanas, decks, fences, pools, etc.) unless adjacent to lake or other water body which might permit a less restrictive setback to be approved by the MARC.

Side Yard: Ten feet (10') to main structure or 10% of the lot width at the front building setback line, whichever is less.

Side Yard

@ Corner: Fifteen feet (15') to main structure.

Driveway: Driveway pavement shall be set back a minimum of 1'-6" from the property line. In retaining wall situations on side lot lines, the driveway may abut the retaining wall on the high side.

4. Sitework. Finished grades shall not direct concentrated water flow (from downspout, pool overflows, sub grade drainage systems, etc.) onto adjacent properties and shall follow the City of McKinney approved grading plans. Anytime a site is altered, it is the builder's responsibility to provide the retainage. Retaining walls are only to be constructed of masonry. If side yard retaining walls are not desired, a slope of 3:1 (max.) must be achieved between the foundation slab and the side yard property line. The MARC reserves the right, upon reasonable advance notice, to require a topographical survey done by a registered surveyor before, during, or after construction.

5. Masonry. Chimneys must be 100% masonry. Also the portion of an elevation which faces a greenbelt, golf course or lake must be 100% masonry. Brick blends may be repeated with a minimum separation of four (4) houses in any direction along the fronting or side/corner streets. All mailboxes are to be located within a masonry structure approved by the MARC.

Each single-family detached residential dwelling (including detached garages) shall have at least seventy-five percent (75%) of the exterior vertical surfaces (excluding windows, doors and roof) composed of approved masonry (i.e., brick, stone stucco). Detached garage exterior walls will be calculated with the main house structure for overall masonry coverage requirement of seventy-five percent (75%).

6. Fences Along Greenbelts, Golf Course or Lakes. With respect to each and every lot which has a side or rear property line coincident with or adjacent to a greenbelt, golf course or lake so as to constitute "open space frontage," fences and walls along the frontage are not required, but if any is installed, it shall comply with the following requirements:

- (A) not more than four feet (4') in height;
 - (B) open metal, primed and painted a flat black color;
 - (C) constructed as indicated in the MASTER DESIGN GUIDELINES,
 - (D) have a gate in the Lot (lakeside lots only) for lakeside access; and
 - (E) be located no closer than 10'-0" to the lake edge.
7. Fences Along Interior Lot Lines. Unless otherwise approved by the MARC, no fence shall exceed six feet (6') in height measured from finished grade. Except for those fences required to be constructed of open metal, all other fences shall be constructed with redwood or Western Red Cedar (#1 or "Standard and Better"). Pickets are to be placed on the exterior face or as specified by the MARC. Posts may be steel pipe columns, cedar or redwood. No pine or spruce fencing materials shall be permitted. Interior lots should have the 6'-0" height wood privacy fence.
8. Roof Drainage. In order to assist in the orderly drainage and removal of roof water and the overall quality of drainage, gutters and downspouts may be required at the discretion and direction of the MARC.
9. Roof. Any proposed composition roof shingles shall be the same or equal to the "Tamco Heritage 30," a 30 year roof, and shall "weigh" at least 280 lbs. per square. The type, quality and color must otherwise be specifically approved by the MARC. Roofs which cover bay windows are required to use copper, anodized aluminum (bronze or black), or an approved factory applied finish.
10. Required Landscaping. Per the MARC approved landscape plan, all landscape is to be installed BY THE BUILDER WITHIN THIRTY (30) DAYS of substantial completion or change of ownership (closing). The Lot areas listed below shall be landscaped with the following size and/or number of shade trees, which shall be from the "highly recommended" or "acceptable" category described within the STONEBRIDGE RANCH Plant Palette (set forth in the Master Design Guidelines).

Lot Area

Minimum Requirement

Front Yard

One row of five-gallon (min.) non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. Two 4½" caliper (min.) large canopy (i.e., red oak, live oak, cedar elm, Bradford pear) shade trees and two 2½" caliper (min.) ornamental trees are required for each front yard.

Adjacent to Greenbelt,

Golf Course or Lake	One row of five gallon (min.) non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. Two 4½" caliper (min.) trees per rear yard, to be located within ten feet (10') of the rear property line.
Corner Yard	One 4½" caliper (min.) shade tree is required to face the "side" street and be located in the side yard (outside the fenced area). One row of non-deciduous (evergreen) five-gallon (min.) shrubbery is required where the foundation is exposed to the street. Where 6' solid wood fences run along the street frontage, one row of five-gallon (min.) evergreen shrubs are required.
AC Units/Mechanical Equipment Meters	One row of non-deciduous (evergreen) five-gallon (min.) shrubbery is required to screen these elements from public view.

11. Landscape Maintenance (Waterfront Lots). Lots on the Lake have a ten foot (10') access easement located along the lake edge for maintenance of the lake by the Stonebridge Ranch Community Association ("SRCA") (see Sketch A). Each homeowner is responsible for maintenance of lawn, landscaping, irrigation and hardscape elements installed within the ten feet (10') easement. Installation of any improvements shall not impede access across the ten feet (10') easement.
12. Irrigation. The MARC requires that each Lot have an automatic irrigation system. Installation of the automatic irrigation system must be concurrent with the finishing stages of the residential dwelling. All automatic irrigation systems shall be designed to have overlapping coverage. Controller devices must be located inside the garage.
13. Sidewalks & Driveways. Unless otherwise approved by the MARC the builder of each single-family home shall construct, install and provide a public sidewalk which shall: (a) be approved (as to size, location and materials) by the MARC; (b) comply with applicable subdivision improvements and City of McKinney, Texas standards; (c) incorporate a "lay-down" curb on corner lots or other similar lots designated by the MARC; and (d) to the extent applicable, conform to and continue the hike-and-bike trail within STONEBRIDGE RANCH. All concrete sidewalks, driveways, walkways and entry paths which are within the public right-of-way must be broom finished as a minimum.
14. Elevations. Each elevation shall be limited to a maximum number of occurrences. As a general rule or objective, each floor plan should have three (3) elevations. Elevations are

allowed to repeat two (three total per elevation) times when there are seven (7) lots of separation along the fronting or side/corner streets between the repeated elevations. Double car garage doors shall not face the street. Single car garage doors may face the street if they are located a minimum of 20' behind the front yard building setback line.

15. Paint Colors. The trim colors of the house will be limited to a specific color family complimentary of the brick selection. Garage doors are suggested to be painted a subtle variation of the primary house color. All exposed exterior flashing is to be painted a color to match the brick color. Roof vents are to be painted a color to match the roof color. Chimney caps are to be painted a color to match the brick.
16. Detached Garages. That portion of the elevation/s which faces the street, greenbelt, golf course or lake must be 100% brick. Elevations that are bricked are required to "return" the brick around the corner of each adjacent elevation a minimum of 2'-0". Where the brick is terminated on the adjacent elevation, a cedar fence shall perpendicularly intersect the end of the terminated brick. The canopy between the main house structure and the detached garage is required to provide brick vertical support columns when the canopy span is greater than 14'.

Detached Garage Setback Requirements. Rear yard greenbelt, golf course or lake - 20' (min.); rear yard interior - 10' (min.); and side yard 10' (min.).

Garages located on the rear side of the house when adjacent to the greenbelt, golf course or lake may be required to be set back from the rear house line and/or to have windows or other features to continue the character of the house across the entire elevation. Garage doors, driveways, and parking aprons must not be visible from adjacent greenbelt, golf course or lake.

17. Homebuilder Construction. Please refer to the most recent publication of the Construction Site Policy.

SUBDIVISION DESIGN GUIDELINES
REVISION LOG
LAKESIDE CROSSING

DATE	DESCRIPTION
3/13/00	Original Document
12/15/00	Revised Ppg. 3 - side yard setback; Ppg. 6 removed reference to Sketch A and word "centered" from (D); Ppg 14 changed repeat to 7 lots of separation.