

**SUBDIVISION DESIGN GUIDELINES**

FOR

**LAKE POINT**

AT

**STONEBRIDGE RANCH**

**SUBDIVISION DESIGN GUIDELINES  
FOR  
LAKE POINT**

These Subdivision Design Guidelines are designed specifically for LAKE POINT Subdivision and are promulgated in accordance with Section 3 of Article VIII of the "Consolidated and Amended Master Declaration of Covenants, Conditions, Restrictions, Easements, Charges and Liens on and for STONEBRIDGE RANCH" (the "Master Declaration") which instrument was recorded on October 29, 1992 as Instrument No. 92-0076613 in the Public Real Estate Records of Collin County, Texas and which is incorporated herein by reference for all purposes.

The primary purpose of these Subdivision Design Guidelines is to establish a design framework which the individual homebuilder or homeowner will use as a guide for site improvement, with latitude and flexibility (on the one hand) balanced against preserving the integrity of STONEBRIDGE RANCH (on the other hand). These Subdivision Design Guidelines will, hopefully, serve to guide, inform, aid and inspire to the same extent as they serve to prohibit, restrict and require. While some features are mandated, it should be understood that the Master Architectural Review Committee ("MARC") may make judgments to reduce or waive any requirement. However, such discretionary approval(s) shall not represent or constitute a binding precedent since no two or more tracts or circumstances are likely to be alike.

1. Minimum Air Conditioned Square Feet (ACSF):

One thousand nine hundred (1,900) acsf.

2. Height Limitation:

Thirty-five feet (35') measured from finished grade at the mid-point of the Lot.

3. Minimum Dwelling Setback Requirements:

Front Yard: Ten feet (10') to main structure.

Rear Yard: Ten feet (10') from rear lot line to main structure (excluding accessory buildings, cabanas, decks, fences, pools, trellises, etc.).

Side Yard: One foot (1') setback from the zero (0) Side Yard & nine feet (9') setback from the other side yard.

Side Yard  
on Corner: Fifteen feet (15').

4. Foundation Survey. An existing grade topographical survey by a registered surveyor is not initially required to be submitted by the builder/owner unless, prior to the commencement of construction, the MARC should foresee potential grading problems. However, the MARC reserves the right, upon reasonable advance notice, to require a topographical survey done by a registered surveyor before, during or after construction.
5. Sitework. Finished grades shall not direct concentrated water (i.e., downspouts, sub grade drainage systems) flow onto adjacent properties and should be able to follow the City of McKinney approved grading plans. Anytime a site is altered, it is the builder's responsibility to provide the retainage. Retaining walls are only to be constructed of stone or masonry. If side yard retaining walls are not desired, a slope of 3:1 (max.) must be achieved between the foundation slab and the side yard property line.
6. Masonry. Unless otherwise specifically approved by the MARC, each single-family detached residential dwelling shall have at least eighty-five percent (85%) of the exterior vertical surfaces (excluding windows, doors and roof) composed of approved masonry (brick, stone, stucco). The entire exterior vertical surfaces of chimneys shall be composed of masonry unless specifically modified, reduced or waived by the MARC. All elevations which face the golf course and street shall be 100% masonry. Approved colors will be limited to a specific color family which may allow four to six brick and/or stucco selections.
7. Fences and Walls Along Lake/Golf Course. With respect to each and every Lot which has a side or rear property line coincident with, adjacent to, or close to a lake/golf course so as to generally constitute "lake or golf course frontage", fences and walls along the frontage (which are not otherwise constructed by the developer) are required and must comply with the following requirements:
  - A. Must be 59" (inches) in height;
  - B. wrought-iron to be primed and painted a flat black color; and
  - C. the other standards applicable to matching the perimeter fence previously installed by the developer.

***\*\*No gate, opening or access may be provided through any fence onto the golf course unless otherwise approved by the MARC.***

Swimming pools, spas and reflecting pools are not permitted inside of electrical easements and must be set back at least three feet (3') from the golf course rear property line.

8. Fence Height and Materials. Unless otherwise approved by the MARC, no fence shall exceed six feet (6') in height measured from finished grade. Except for those fences required to be constructed of metal, all other fences shall be constructed with redwood, Western Red Cedar (#1 or "Standard and Better") with pickets placed on the exterior face. Posts may be steel (clad with wood), cedar or redwood. No pine or spruce fencing materials shall be

permitted.

Lot 26, Block A has the option of a standard fence as described herein or a 4' wrought iron fence adjacent to the drainage area.

9. Roof Drainage. In order to assist in the orderly drainage and removal of roof water and the overall quality of drainage, gutters and downspouts are required on all homes.
10. Roofs. Any proposed composition roof materials (i.e., Tamco Heritage II) shall be a 25-year type roof and "weigh" approximately 220 to 240 lbs. per square. The type, quality and color must be specifically approved by the MARC. Roofs which cover bay windows are required to use copper, anodized aluminum (bronze or black), or a MARC approved factory applied finish.
11. Required Landscaping. Per the MARC approved landscape plan, all landscape is to be installed **BY THE BUILDER WITHIN THIRTY (30) DAYS OF SUBSTANTIAL COMPLETION OR CHANGE OF OWNERSHIP (CLOSING)**. The Lot areas listed below shall be landscaped with the following size and/or number of shade trees, which shall be from the "highly recommended" or "acceptable" category described within the **STONEBRIDGE RANCH Plant Palette** (set forth in the Master Design Guidelines), varying in size with an average caliper of 4" and with no tree smaller than 2½" caliper (unless the MARC has otherwise approved a multiple trunk cluster):

Lot Area

Minimum Requirement

Front Yard

One row of five gallon non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. A total of one (1) 4½" caliper (min.) large canopy (i.e., red oak, live oak, cedar elm, Chinese pistachio) shade trees are required for each front yard. In addition to the large canopy tree previously mentioned, 1" ornamental tree trunk caliper is required per each 15 linear feet of front property line. The smallest canopy tree caliper permitted is 1 ½".

Adjacent to Greenbelt  
and Golf Course

One row of five (5) gallon non-deciduous (evergreen) shrubbery located along the foundation excluding porches and patios. A total of one 4½" (min.) caliper tree per rear yard, to be located within ten feet (10') of the rear property line. Trees may also be planted on the golf course or the Lake Point

Sub-Association greenbelt side of the property line within five feet (5') of the property line with prior written approval of the golf course or Association.

Corner Yard

A total of one (1) 4½" (min.) caliper shade tree is required to face the "side" street. One row of non-deciduous five (5) gallon shrubbery is required where the foundation is exposed to the street.

12. Irrigation. The MARC requires that each Lot have a front-yard automatic irrigation system. Corner Lots must have a front and side yard automatic irrigation system. Further, each Lot which has a rear or side yard adjoining Greenway Frontage areas (e.g. golf course, park, greenbelt, open area) must also have an automatic irrigation system installed within such area concurrent with the finishing stages of the residential dwelling and the plans and specifications to be submitted to the MARC must show the proposed irrigation arrangement. All automatic irrigation systems shall be designed by a licensed irrigator and are required to have overlapping coverage. Controller devices must be located inside the garage area. Irrigation systems must be properly maintained and repaired at all times.
13. Sidewalks & Driveways. Unless otherwise approved by the MARC, the builder of each single-family home shall construct, install and provide a public sidewalk which shall: (a) be approved (as to size, location and materials) by the MARC; (b) comply with applicable subdivision improvements and City of McKinney, Texas standards; (c) incorporate a "lay-down" curb on corner lots or other similar lots designated by the MARC; and (d) to the extent applicable, conform to and continue the hike-and-bike trail within STONEBRIDGE RANCH. All concrete sidewalks, driveways, walkways and entry paths which are not within the public right-of-way must be broom-finished as a minimum.
14. Elevations. Each elevation or distinctive detail shall be limited to a minimum number of occurrences per street scene. As a general rule or objective, each floor plan should have three (3) elevations. Elevations shall not repeat without at least 3 intervening homes of sufficient dissimilarity. The intent of this guideline is to avoid the negative "look alike" effect of frequent repetition, while allowing sufficient latitude for the builder in satisfying market demand.
15. Paint Colors. The trim colors of the house will be limited to a specific color family complimentary of the brick selection. Garage doors should be painted a subtle variation of the primary house color. All exposed exterior flashing is to be painted a color to match the roof color or the brick color. Roof vents are to be painted a color to match the roof color.
16. Address Plaques. The address plaques are to be made of cast stone and mounted on a conspicuous vertical surface close to the front door.

17. Homebuilder Construction Hours. Please refer to the most recent publication of the Construction Site Policy.

**SUBDIVISION DESIGN GUIDELINES  
REVISION LOG  
LAKE POINT**

<b>DATE</b>	<b>DESCRIPTION</b>
1/25/96	Original Document
2/21/96	Revision: Ppg. 7 changed to allow stucco
3/1/96	Further clarification of Paragraph 7
3/10/00	Page 1, 2 <sup>nd</sup> paragraph - Deleted ... <i>"value and"</i> integrity... Section 2 (Maximum Square Footage Requirement) - Deleted
06/18/2015	Updated landscaping and fencing requirements to meet current